

Features

- Fast switching
- Low Gate Charge
- Improved dv/dt capability
- 100% avalanche tested
- Green Device Available


Product Summary



V_{DS}	650	V
I_D	10	A
$R_{DS(ON)}$ Typ (at $V_{GS}=10V$)	0.8	Ω

Applications

- Switch Mode Power Supply (SMPS)
- Uninterruptible Power Supply (UPS)
- Power Factor Correction (PFC)
- AC to DC Converters



Absolute Maximum Ratings($T_C=25^\circ C$, unless otherwise noted)

Parameter	Symbol	Rating	Units
Drain-Source Voltage	V_{DS}	650	V
Gate-Source Voltage	V_{GS}	± 30	V
Continuous Drain Current ¹	$I_D@T_C=25^\circ C$	10	A
Pulsed Drain Current ²	I_{DM}	40	A
Single Pulse Avalanche Energy ³	EAS	720	mJ
Total Power Dissipation ⁴	P_D	65	W
Storage Temperature Range	T_{STG}	-55 to 150	$^\circ C$
Operating Junction Temperature Range	T_J	-55 to 150	$^\circ C$

Thermal Characteristics

Parameter	Symbol	Value	Unit
Thermal Resistance Junction-Ambient	$R_{\theta JA}$	62.5	$^\circ C/W$
Thermal Resistance Junction-Case	$R_{\theta JC}$	2.07	$^\circ C/W$

Electrical Characteristics (T_J=25°C, unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V, I _D =250uA	650	---	---	V
Static Drain-Source On-Resistance ²	R _{DS(ON)}	V _{GS} =10V, I _D =5A	---	0.8	1	Ω
Gate Threshold Voltage	V _{GS(th)}	V _{GS} =V _{DS} , I _D =250uA	2	---	4	V
Drain-Source Leakage Current	I _{DSS}	V _{DS} =650V, V _{GS} =0V, T _J =25°C	---	---	1	uA
Gate-Source Leakage Current	I _{GSS}	V _{GS} =±30V, V _{DS} =0V	---	---	±100	nA
Total Gate Charge	Q _g	V _{DD} =520V, V _{GS} =10V, I _D =10A	---	38	---	nC
Gate-Source Charge	Q _{gs}		---	33	---	
Gate-Drain Charge	Q _{gd}		---	7	---	
Turn-On Delay Time	T _{d(on)}	V _{DD} =325V, R _G =25Ω, I _D =10A	---	23	---	ns
Rise Time	T _r		---	14	---	
Turn-Off Delay Time	T _{d(off)}		---	90	---	
Fall Time	T _f		---	30	---	
Input Capacitance	C _{iss}	V _{DS} =25V, V _{GS} =0V, f=1MHz	---	1570	---	pF
Output Capacitance	C _{oss}		---	138	---	
Reverse Transfer Capacitance	C _{rss}		---	15	---	

Drain-Source Diode Characteristics

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Diode Forward Voltage ²	V _{SD}	V _{GS} =0V, I _S =10A, T _J =25°C	---	---	1.5	V
Reverse recovery time	t _{rr}	I _F =10A, diF/dt=100A/μs	---	480	---	ns
Reverse recovery charge	Q _{rr}		---	3.5	---	nC

Note:

- 1.The data tested by surface mounted on a 1 inch² FR-4 board with 2OZ copper.
- 2.The data tested by pulsed, pulse width ≤ 300us, duty cycle ≤ 2%
- 3.The power dissipation is limited by 150°C junction temperature

Typical Characteristics

Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. BV_{DSS} vs. Temperature




Figure 4. On-Resistance vs. Temperature




Figure 5. Gate Charge




Figure 6. Body Diode Forward Voltage




Figure 7. Capacitance Characteristics




Figure 8. Transient Thermal Impedance






Figure 9. Maximum Safe Operating Area



TO-220F Package Outline Dimensions



Symbol	Dimensions (unit:mm)			Symbol	Dimensions (unit:mm)		
	Min	Typ	Max		Min	Typ	Max
A	4.40	4.70	5.00	H1	6.70 REF		
A1	2.30	2.55	2.80	L	12.30	12.98	13.30
A2	0.30	0.50	0.70	L1	2.95	3.10	3.50
A4	2.45	2.80	3.05	phi P	3.03	3.20	3.50
c	0.30	0.50	0.70	phi P3	3.15	3.45	3.65
c1	1.20	1.30	1.40	b1	1.10	1.30	1.45
D	15.40	15.90	16.40	b2	0.60	0.80	1.00
E	9.86	10.16	10.46	F3	3.05	3.30	3.55
e	2.54 BSC			G3	1.15	1.35	1.55

Printing Information

ATC =====Brand

XXXXXXX =====Material Code

XXYY =====XX Representative Year
 YY Representative Weeks